



# ODO50-BLE

## 1. INSTALLING ODO50-BLE

There are two options.

### 1. DIRECTLY INTO THE OBD-II OUTLET

- › Make sure the vehicle's ignition is turned off.
- › Locate the OBD-II outlet. The location may vary for different manufacturers, models, and production years.
- › Carefully insert the ODO50-BLE into the OBD-II outlet.

**WARNING:** Might not be compatible with certain vehicle models. Check with your dealer.

### 2. OPTIONAL: WITH THE ADAPTER PROVIDED

Connect the ODO50-BLE to the cigarette lighter socket with the OBD-II adapter (12V) (not included).

**Note:** Idle time is not accounted for when connected to the cigarette lighter.

If you plan on not using your vehicle for longer than a week, it is strongly recommended you disconnect your ODOTRACK device in order to keep the car battery from self-discharging.

## 2. SET-UP

The device comes with 4 power lights: Cellular (red), GPS (green), OBD (yellow), and Bluetooth (blue). If the device is installed correctly, you'll see the power lights of the GPS connection and the cellular connection blink (for about 1 second).

## 3. CONFIRMATION

- ✓ Log in to your account ([odotrack.com](http://odotrack.com))
- ✓ Select the ODOTRACK module
- ✓ Confirm your vehicle's location

Wait 30 minutes or so after installing your new device for it to start transmitting its position. The delay may vary depending on the cellular network.

## 4. LOOK UP YOUR TRIPS

Visit the online ODOTRACK application at [www.odotrack.com/login](http://www.odotrack.com/login) to complete activation and to view or print your trip reports.

**NOTE:** The password is case-sensitive.

E-mail:

Password:

Then click the **LOG IN** button

## 5. DOWNLOAD THE ODOhybrid APP

Optimize your experience with the ODOhybrid app available in the Apple Store and Google Play. This app lets you interact with your ODO50-BLE device. It also allows you to edit your current trip information in real time.

## 6. ODOconstruction CLIENTS

Confirm your worksites via the mobile website at [c.odotrack.ca](http://c.odotrack.ca).



### MICRO-USB PORT (exclusive to ODOTRACK use)

This port is designed for device configuration and updates. It should not be used as a plugin.



## CERTIFICATIONS

FCC, PTCRB, CE and RoHS